



## DATA ACQUISITION SYSTEM MPK II



Management  
System  
ISO 9001:2015

www.tuv.com  
ID: 0091005312



**PAULWEGENER**  
MESSTECHNIK SEIT 1921

# TECHNICAL DATA SHEET MPK II

## Data acquisition system

Carrying case / material	Peli 1450 (polypropylene)
Dimensions	40.6 x 33 x 17.4 cm (w x h x d)
Degree of protection	IP 67
Weight (inclusive rechargeable battery)	approx. 9 kg
Power supply	lithium ion battery 6.200 mAh (overcharge and depth discharge protection)
Running time	up to 1 month
Printer	built-in thermal printer (printout 110 x 295 mm)
Data logger	MPK 2.0
Data memory / internal	2 MB
Backup memory / internal	4 GB
Backup memory / external	USB stick 2.0
Storage interval	1s - 1h (arbitrary)
Storage mode	ring buffer or linear storage unit
Display	graphics TFT 7, 0" capacitive
Operation	touch display or PC
Version	E/ A push button and GPS receiver
Accessories	charging cable and evaluation software
Transducers	built-in pressure and temperature transducer, configurable port for external transducers (optional) external temperature transducer (optional)
Temperature measuring ranges	- 10 °C up to + 40 °C / - 20 °C up to + 60 °C
Pressure measuring ranges	0...50 mbar up to 0...70 bar 0...40 bar up to 0...1000 bar
Accuracy	0,05% up to 1% v.E. (see PWB standard transducers)



Händlerstempel



**PAULWEGENER**  
MESSTECHNIK SEIT 1921

Adresse | Paul Wegener GmbH | Marienstraße 24 | 06493 Ballenstedt  
Telefon | +49 39483 96-300  
Fax | +49 39483 96-400  
Internet | www.paul-wegener.de  
E-Mail | info@paul-wegener.de